



US006950988B1

(12) **United States Patent**  
**Hawkins et al.**

(10) **Patent No.: US 6,950,988 B1**  
(45) **Date of Patent: Sep. 27, 2005**

(54) **MULTI-CONTEXT ITERATIVE DIRECTORY FILTER**

(75) Inventors: **Jeffrey C. Hawkins**, Redwood City, CA (US); **Thomas B. Bridgwater**, San Francisco, CA (US); **Robert Y. Haitani**, Menlo Park, CA (US); **Srikiran Prasad**, San Francisco, CA (US); **William B. Rees**, Menlo Park, CA (US)

5,127,041 A	6/1992	O'Sullivan	379/59
RE34,034 E	8/1992	O'Sullivan	375/59
5,189,632 A	2/1993	Paajanen et al.	364/705.05
5,227,614 A	7/1993	Danielson et al.	
5,249,218 A	9/1993	Sainton	375/59
5,334,824 A	8/1994	Martinez	
5,335,276 A	8/1994	Thompson et al.	380/21

(Continued)

#### FOREIGN PATENT DOCUMENTS

(73) Assignee: <b>Handspring, Inc.</b> , Mountain View, CA (US)	CA	2187050	5/1997	.....	H05K/5/03
	EP	0149762 A1	7/1986		
	EP	0 813 328 A2	12/1997	.....	H04M/1/23

(Continued)

#### OTHER PUBLICATIONS

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 419 days.

U.S. Appl. No. 07/831,671, Claims 25–55 only.  
U.S. Appl. No. 09/670,696, Claims 25–46 only.  
U.S. Appl. No. 09/813,165, Claims 24–29 only.

(Continued)

#### Related U.S. Application Data

(60) Provisional application No. 60/297,817, filed on Jun. 11, 2001.

(51) **Int. Cl.**<sup>7</sup> ..... **G09G 5/00**

(52) **U.S. Cl.** ..... **715/700**; 715/810; 715/816; 707/1

(58) **Field of Search** ..... 345/701, 773, 345/864; 707/3, 6, 7, 1; 715/700, 810, 816

#### (56) References Cited

##### U.S. PATENT DOCUMENTS

4,279,021 A	7/1981	See et al.	
4,415,065 A	11/1983	Sandstedt	
4,545,023 A	10/1985	Mizzi	364/709
4,587,630 A	5/1986	Straton et al.	
4,725,694 A	2/1988	Auer et al.	
4,916,441 A	4/1990	Gombrich	
4,972,457 A	11/1990	O'Sullivan	379/59
5,067,164 A	11/1991	Denker et al.	
5,101,439 A	3/1992	Kiang	

*Primary Examiner*—John Cabeca


*Assistant Examiner*—Ting Zhou

(74) *Attorney, Agent, or Firm*—Fenwick & West LLP

#### (57) ABSTRACT

On a device having keys with multiple values, a user may perform either an iterative directory filtering operation or a direct-dial operation, without specifying which of the operations is intended. The invention thereby allows the user to perform any of a number of different operations to specify a number to be dialed or to identify a directory record, without requiring the user to specify a mode. The invention determines which of the operations the user intends by analyzing the entered keystrokes, and activates the appropriate feedback and functionality for the determined operation. The invention further performs iterative directory filtering on multiple fields concurrently, including derived fields and combination fields.

**98 Claims, 15 Drawing Sheets**



# US 6,950,988 B1

Page 2

## U.S. PATENT DOCUMENTS

5,353,334 A	10/1994	O'Sullivan	379/59	D439,232 S	3/2001	Ledingham et al.
5,367,563 A	11/1994	Sainton	379/98	6,198,783 B1	3/2001	Campana, Jr. et al. .... 375/346
D354,478 S	1/1995	Miyahara		6,204,848 B1	3/2001	Nowlan et al.
5,379,057 A	1/1995	Clough et al.		RE37,141 E	4/2001	O'Sullivan ..... 455/557
5,392,447 A	2/1995	Schlack et al.		D440,959 S	4/2001	Wolf et al.
D359,734 S	6/1995	Nagele et al.	D14/138	6,219,694 B1	4/2001	Lazaridis et al. .... 709/206
5,436,960 A	7/1995	Campana, Jr. et al.	379/58	D442,156 S	5/2001	Lee
5,438,611 A	8/1995	Campana, Jr. et al.	379/58	D443,865 S	6/2001	Kim
5,446,759 A	8/1995	Campana, Jr. et al.	375/267	D446,199 S	8/2001	Xu et al.
5,465,401 A	11/1995	Thompson		6,272,190 B1	8/2001	Campana, Jr. et al. .... 375/345
5,479,472 A	12/1995	Campana, Jr. et al.	379/58	6,278,442 B1	8/2001	Griffin et al. .... 345/169
5,485,373 A	1/1996	Davis et al.		6,288,718 B1 *	9/2001	Laursen et al. .... 345/800
5,496,992 A	3/1996	Madan et al.		6,295,372 B1	9/2001	Hawkins et al.
5,550,715 A	8/1996	Hawkins	362/31	6,295,460 B1	9/2001	Nagel et al. .... 455/557
5,584,054 A	12/1996	Tyneski et al.	455/89	6,307,548 B1 *	10/2001	Flinchem et al. .... 345/811
5,594,640 A	1/1997	Capps et al.		D450,307 S	11/2001	Xu et al.
5,625,670 A	4/1997	Campana, Jr. et al.	379/58	6,317,592 B1	11/2001	Campana, Jr. et al. .... 455/412
5,631,946 A	5/1997	Campana, Jr. et al.	379/58	6,330,618 B1	12/2001	Hawkins et al.
5,640,146 A	6/1997	Campana, Jr. et al.	340/573	D454,349 S	3/2002	Makidera et al.
5,640,444 A	6/1997	O'Sullivan	379/59	D455,135 S	4/2002	Hyun
5,650,769 A	7/1997	Campana, Jr. et al.	340/573	6,370,518 B1 *	4/2002	Payne et al. .... 707/1
D385,875 S	11/1997	Harris et al.		D456,805 S	5/2002	Ono et al.
D386,497 S	11/1997	Huslig et al.		6,397,078 B1	5/2002	Kim
5,694,428 A	12/1997	Campana, Jr. et al.	375/260	6,477,482 B1	11/2002	Maupin et al.
5,710,798 A	1/1998	Campana, Jr. et al.	375/347	6,489,950 B1	12/2002	Griffin et al.
5,714,937 A	2/1998	Campana, Jr. et al.	340/573	6,549,304 B1	4/2003	Dow et al.
5,717,725 A	2/1998	Campana, Jr. et al.	375/347	6,611,697 B1	8/2003	Ewing et al.
5,722,059 A	2/1998	Campana, Jr. et al.	455/226.2	6,662,244 B1	12/2003	Takahashi
5,722,064 A	2/1998	Campana, Jr. et al.	455/351	6,725,060 B1	4/2004	Chhatrivala et al.
D393,856 S	4/1998	Lee et al.	D14/138	6,727,916 B1	4/2004	Ballard
5,742,644 A	4/1998	Campana, Jr. et al.	375/316	2001/0027121 A1	10/2001	Boesen
5,745,532 A	4/1998	Campana, Jr. et al.	375/347	2002/0021311 A1 *	2/2002	Shechter et al. .... 345/864
5,751,773 A	5/1998	Campana, Jr. et al.	375/346	2002/0086702 A1	7/2002	Lai et al.
D395,300 S	6/1998	Yamazaki et al.		2002/0097227 A1	7/2002	Chu et al.
5,761,621 A	6/1998	Sainton	455/453	2002/0126097 A1 *	9/2002	Savolainen ..... 345/168
5,797,089 A	8/1998	Nguyen		2002/0186262 A1	12/2002	Itavaara et al.
5,797,098 A	8/1998	Schroeder et al.		2003/0123627 A1	7/2003	Pinard et al.
5,805,633 A	9/1998	Uddenfeldt	375/202	2004/0047505 A1	3/2004	Ghassabian
5,812,117 A	9/1998	Moon	345/169			
5,818,437 A *	10/1998	Grover et al.	345/811			
5,819,172 A	10/1998	Campana, Jr. et al.	455/412			
5,825,353 A	10/1998	Will				
5,825,675 A	10/1998	Want et al.				
5,854,985 A	12/1998	Sainton et al.	455/553			
5,864,805 A	1/1999	Chen et al.				
5,884,323 A	3/1999	Hawkins et al.				
D408,021 S	4/1999	Haitani et al.				
D408,030 S	4/1999	Richards et al.				
D409,185 S	5/1999	Kawashima				
D410,486 S	6/1999	Takahata et al.				
5,966,671 A	10/1999	Mitchell et al.				
D416,001 S	11/1999	Tal et al.				
D416,256 S	11/1999	Griffin et al.				
5,983,073 A	11/1999	Ditzik				
5,990,872 A	11/1999	Jorgenson et al.				
6,000,000 A	12/1999	Hawkins et al.				
6,006,274 A	12/1999	Hawkins et al.				
D421,744 S	3/2000	Ono				
6,040,829 A	3/2000	Croy et al.				
6,043,760 A	3/2000	Laakkonen				
D423,468 S	4/2000	Jenkins				
6,058,304 A	5/2000	Callaghan et al.	455/422			
6,067,451 A	5/2000	Campana, Jr. et al.	455/412			
D432,099 S	10/2000	Loh et al.				
D432,535 S	10/2000	Loh et al.				
D433,016 S	10/2000	Matsuda et al.				
6,134,453 A	10/2000	Sainton et al.	455/553			
6,141,540 A	10/2000	Richards et al.				
6,169,485 B1	1/2001	Campana, Jr. et al.	340/573			
6,188,789 B1	2/2001	Marianetti, II et al.	382/189			

## FOREIGN PATENT DOCUMENTS

EP	0 840 934 B1	4/1999	.....	H01H/13/70
WO	WO 94/10678	5/1994	.....	G09G/5/14
WO	WO 94/16408	7/1994	.....	G06K/9/00
WO	WO 96/01453	1/1996	.....	G06K/9/00
WO	WO 00/65445	11/2000	.....	G06F/11/00

## OTHER PUBLICATIONS

BlackBerry Handheld Users Guide, Sep. 7, 1999.  
 BlackBerry Developer's Guide SDK User's Guide Version 2.0 (Data TAC), Jun. 12, 2000.  
 BlackBerry Desktop Software Installation and Getting Started Guide, Feb. 5, 1999.  
 BlackBerry Enterprise Server Software Installation and Getting Started Guide, Sep. 29, 1999.  
 Compaq Product Information, *iPAQ Pocket PC Options*, retrieved from internet: [www.compaq.com/products/handhelds](http://www.compaq.com/products/handhelds), Nov. 13, 2001.  
 Choi, H., *First Look: Samsung I300 Cellphone/PDA*, retrieved from internet [www.techtv.com](http://www.techtv.com), Mar. 28, 2001.  
 Handspring Product Information: *VisorPhone The Springboard Module that Transforms your Visor into an Extraordinary Phone*, (2000).  
 Handspring, *Sprint and Airprime Delivery First Wireless CDMA Phone and Data Module for the Handspring Visor*, retrieved from the internet [www.handspring/pr59.jhtml](http://www.handspring/pr59.jhtml) Aug. 2, 2001.  
 Handspring VisorPhone Module User Guide, (2001).  
 U.S. Appl. No. 09/835,464, Claims 1-6 only.

U.S. Appl. No. 09/953,211, Claims 26–30 only.

IBM Technical Disclosure Bulletin: *SimpleUser Interface to a Cellular Telephone*, retrieved from internet, Oct. 2001.

IBM Technical Disclosure Bulletin: *Inexpensive Personal Digital Assistant*, retrieved from internet, Apr. 2001.

Kyocera's Smartphone Series, retrieved from internet [www.kyocera-wireless.com](http://www.kyocera-wireless.com), Apr. 2001.

Mossberg, W., *Samsung Embeds Cellphone Inside Palm in New I300 Device*, retrieved from internet <http://www.ptech.wsj.com/archive/ptech-20010830.html>, Oct. 26, 2001.

Newspaper Article: *Ways to Escape Multiple-Remote Hell*, San Jose Mercury News, Jun. 14, 2001.

Nokia 9110 Accessories Quick Guide Instruction Manual.

Sprint PCS User Guide—Samsung Model SCH-8500.

Tam, P., "Palm, Motorola to Make PDA Cell Phones", retrieved from internet <http://www.zdnet.com/zdnn/stories/news/0,4586,2631800,00.html>, Sep. 25, 2000.

Technical White Paper BlackBerry Enterprise Edition for Microsoft Exchange, Version 2.1, (2001).

Technical White Paper BlackBerry Enterprise Server for Microsoft Exchange, Version 2.1, (2001).

Tucows PDA Phone GSM Dailer: GSM Dailer 1.0 retrieved from internet <http://pds.rcp.net/pe/pocket/preview154208.html>, Jun. 19, 2001.

*American Programmer*, N.Y., American Programmer, Inc. (Dec. 1991), pp. 4–33.

*At Last, Technology Harnesses [sic] One of the Most Powerful [sic] Forces known to Man.*, Foster City, GO Corporation, 1991, 14 pages.

AT&T New Release, *NCR Cuts Price of 3170 Notebook Computer 11 to 19 Percent* [online]. (Mar. 8, 1993), Retrieved from the Internet: <URL:<http://www.att.com/press/0393/930308.nca.html>> 2 pages.

Carr, R.M., *The Point of the Pen*, Byte (Feb. 1991, Reprinted), 10 pages.

Cullen, A., *Connecting With Your EO Cellular Module*, Mountain View, EO, Inc., 1992, 1993, pp. ii–33.

Cullen, A., *Getting Started With Your EO Personal Communicator*, Mountain View, EO, Inc., 1992, 1993, pp. ii–74.

Cullen, A., *Lookup Guide to the EO Personal Communicator*, Mountain View, EO, Inc., 1992, 1993, pp. ii–320.

*Go Corporation Information Statement*, (Nov. 8, 1993), 114 pages.

*IBM Selects Racotek Data/Voice Communications Services to Interface With Touchmobile Product*, PR Newswire (Jan. 25, 1993), 2 pages.

*IBM TouchMobile Information and Planning Guide*, International Business Machines Incorporated (Mar. 1993), 20 pages.

*IBM TouchMobile Solution for Data Capture and Communication, Keeping Your Business Moving in the 90s*, International Business Machines Incorporated (Jan. 1993), 13 pages.

*IBM'S Touchmobile Helps Field Workers Collect Data at the Touch of a Finger*, PR Newswire (Jan. 26, 1993), 2 pages.

MacNeill, D., *Messaging Card and NewtonMail: We Pick Up and Deliver*, *On The Go Magazine* [online]. (Oct. 13, 1993), Retrieved from the Internet: <URL:<http://www.pen-computing.com/Newton/NewtonNotes2.html>> 2 pages.

MacNeill, D., *Wireless Newton Technology Goes to Work*, *On The Go Magazine* [online]. (Sep. 8, 1993), Retrieved from the Internet: <URL:<http://www.pencomputing.com/NewtonNotes1.html>> 2 pages.

Maki, K., *The AT&T EO Travel Guide*, N.Y., John Wiley & Sons, Inc., 1993, pp. iii–555.

Schlender, B. R., *Hot New PCs That Read Your Writing*, *Fortune* (Feb. 11, 1991, Reprinted), 6 pages.

Stock, R., *The World of Messaging An Introduction to Personal Communications*, Mountain View, EO, Inc., 1992, 1993, pp. ii–69.

SyncML Website Introduction Page, SyncML Initiative LTD., [Retrieved on Oct. 24, 2002]. Retrieved from the Internet: <URL:<http://www.syncml.org/about-intro.html>>, 2 pages.

SynML Sync Protocol [Retrieved on Dec. 7, 2000]. Retrieved from the Internet: <URL:[http://www.syncml.org/docs/syncml\\_protocol\\_v10\\_20001207.pdf](http://www.syncml.org/docs/syncml_protocol_v10_20001207.pdf)>, 60 pages.

SynML Sync Protocol Version 1.0.1 [Retrieved on Jun. 15, 2001]. Retrieved from the internet: <URL:[http://www.syncml.org/docs/syncml\\_protocol\\_v101\\_20010615.pdf](http://www.syncml.org/docs/syncml_protocol_v101_20010615.pdf)>, 61 pages.

Wireless Application Protocol, Service Loading, WAP-168-ServiceLoad-200110731-a, Version 31—Jul.—2001, 18 pages.

Wireless Application Protocol, Service Indication, WAP-167-ServiceInd-200110731-a, Version 31—Jul.—2001, 28 pages.

Wireless Application Protocol, Push Message, WAP-251-PushMessage-20010322-a, Version 22—Mar.—2001, 14 pages.

Wireless Application Protocol, WAP-Sync-Spec. Data Synchronisation Specification, WAP-234-SYNC-20010530-a, Version 30—May—2001, 11 pages.

Wireless Application Protocol, Wireless Application Protocol, Wireless Markup Language Specification Version 1.3, WAP WML, WAP-191-WML, Feb. 19, 2000, 110 pages.

\* cited by examiner




FIG. 1








FIG. 2

**FIG. 3A**

**FIG. 3B**

**FIG. 3C**



**FIG. 4**




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 6E




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 8A







FIG. 8B








FIG. 9A




FIG. 9B




FIG. 9C




FIG. 9D

## MULTI-CONTEXT ITERATIVE DIRECTORY FILTER

### CROSS-REFERENCE TO RELATED APPLICATIONS

The present application claims priority from provisional U.S. patent application Ser. No. 60/297,817 for "Handheld Device," filed Jun. 11, 2001, the disclosure of which is incorporated herein by reference.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention is related to retrieving directory records, and more particularly to multi-context iterative directory filter techniques including 1) concurrent operation in a directory filtering mode and a direct-dial mode, without requiring the user to specify which mode is intended; and 2) concurrent filtering based on two or more directory fields.

#### 2. Description of the Background Art

Many handheld devices, such as personal digital assistants (PDAs), cellular telephones, laptop computers, and the like, provide electronic directories of contact information. Such directories are often capable of storing a large number of entries, or records, each corresponding to an individual or business. Many types of information may be stored in directory records, such as names, postal addresses, telephone numbers, e-mail addresses, and other contact information. Using an interface for interacting with the directory, users can add, edit, and delete records as needed, to keep the directory up to date.

Users may retrieve records stored in electronic directories in a variety of ways. The particular mechanics for retrieving directory records depend upon many factors, including for example the nature and purpose of the device, the hardware configuration and design of the device (including display, keyboard, and the like), the user interface of the directory software, the nature of the user's contemplated interaction with the device, the context in which the interaction takes place, the user's preferences and level of expertise in operating the device, and the like. Some common techniques for retrieving a directory record include: scrolling through a displayed list; searching for one or more keywords entered by the user; pressing a key corresponding to an initial letter of the person's name; typing the first few letters of the person's name; and the like.

One technique for retrieving a directory record is iterative filtering. The user enters letters in succession, and the device displays directory records that match the letters entered. As the user enters each letter, the number of displayed records is iteratively filtered, so that fewer and fewer records tend to be displayed. When only one record is displayed, it may be automatically selected. At any time during the iterative filtering, the user can navigate (e.g. by scrolling) among displayed records to select the desired record.

For example, suppose a directory contains the following records (among others):

Rafferty, Janine  
Raiklen, Bill  
Rainey, Mark  
Rea, Stacy  
Sackman, Eric

A user seeking to retrieve the directory record for Bill Raiklen would enter each letter in the person's last name in sequence. After entering the first letter, "R", Eric Sackman's

name would be filtered out (since it does not begin with "R"), leaving:

Rafferty, Janine  
Raiklen, Bill  
Rainey, Mark  
Rea, Stacy

After entering the next letter, "A", Stacy Rea's name would be filtered out (since it does not begin with "RA"), leaving:

Rafferty, Janine  
Raiklen, Bill  
Rainey, Mark

After entering the next letter, "I", Janine Rafferty's name would be filtered out (since it does not begin with "RAI"), leaving:

Raiklen, Bill  
Rainey, Mark

Finally, after entering the next letter, K, Mark Rainey's name would be filtered out, so that only Bill Raiklen's name remains. At this point, the directory record for Bill Raiklen could automatically be retrieved or his name automatically selected. Thus, the user is able to specify one of the listed directory records with a minimum of keystrokes. The user need not enter the remaining letters in Bill Raiklen's name, since the system is now able to determine which directory entry the user is attempting to specify, even though only four keystrokes have been entered.

One limitation of the above-described conventional technique is that the user can only search on one field, in this case the last name. In general, in such iterative filtering operations as provided in the art, filtering is performed with respect to a predefined field (such as last name). Thus, if the user attempts to locate a record by entering keystrokes for a different field (such as first name, for example), the user may fail to retrieve the intended record. Conventional iterative filtering techniques do not generally provide a mechanism for concurrently filtering a directory according to the user's entries as compared with two or more directory fields.

In addition to retrieving records from an electronic directory, many users often dial numbers directly into the device. For example, if a user of a cellular telephone wishes to call someone who is not listed in the user's directory, the user may dial the person's number via a keypad on the telephone. Typically, such an operation is performed in a different mode than the directory lookup mode, so that there is no ambiguity as to which type of operation (directory lookup or direct-dial) the user wishes to perform. Usually, the user must explicitly select which mode is desired, by navigating through displayed menus or by executing commands in accordance with the user interface of the device.

In many handheld devices, multiple-value keys are provided, so as to save space and reduce the total number of keys. For example, some keys may correspond to a numeric value as well as an alphabetic value. Depending on the current mode of operation, pressing the key results in entry of either the numeric value or the alphabetic value. Thus, a dialing mode may be provided for direct entry of a telephone number to be dialed, and a directory retrieval mode may also be provided for retrieving directory records. Both operations may use the same keys; thus, a particular key may have a numeric value for use in the dialing mode and an alphabetic value for use in the directory retrieval mode.

It is often important that tasks such as dialing numbers or locating a particular contact record be as easy as possible to

carry out. Many such handheld devices are used in environments where the user's ability to concentrate on the task of retrieving a directory record is limited, or where the user is attempting to perform such a task while concurrently performing other tasks. Accordingly, it is advantageous for electronic directories to be easily navigated and for records to be easily retrieved.

Requiring explicit selection of a mode can make the device cumbersome and difficult for users to operate. In many environments, users are not familiar with the mode selection requirement, or are operating the device while driving, or are otherwise unable to explicitly select a mode before performing an operation on the device.

What is needed, therefore, is a system, method, and user interface that allows a user to perform any of a plurality of operations, including directory retrieval and direct-dialing, on a device having multiple-value keys, without having to specify a mode before beginning the desired operation. What is further needed is a system, method, and user interface that performs iterative filtering of a directory concurrently with accepting keystrokes for a direct-dial operation. What is further needed is a system, method, and user interface that automatically determines which operation the user intends, so that the user is not required to specify a mode. What is further needed is a system, method, and user interface that allows a user to retrieve directory records according to any of a number of different fields (such as first name, last name, initials, and the like) without having to specify which field is being searched on. What is further needed is a technique for performing iterative filtering of a directory with respect to multiple fields concurrently, including stored fields, derived fields, and/or combination fields.

#### SUMMARY OF THE INVENTION

The present invention performs multi-context iterative directory filtering in a device having multiple-value keys. The user may perform direct-dialing on the same keys that are used for iterative directory filtering. The invention determines which operation the user intends by analyzing the entered keystrokes, and activates the appropriate feedback and functionality for the determined operation. In one aspect, where the determination cannot be made, both types of feedback are shown. In another aspect, where the determination cannot be made, the invention assumes the user is attempting directory filtering. In yet another aspect, where the determination cannot be made, the invention assumes the user is attempting direct-dialing.

In one aspect, the invention compares a user-entered series of keystrokes with a set of directory records, where at least some of the keystrokes are associated with multiple values. Directory records that do not match the keystroke series are filtered out; directory records that do match the keystroke series are displayed. For those keys having multiple values, filtering is performed using each of the possible values, so that a directory record is filtered out only if it fails to match any of the possible values for the keystroke series. As the user enters additional keystrokes, the invention repeats the filtering process against the directory, so that the set of matching directory records tends to decrease in size with successive keystrokes.

In one aspect, if the user-entered series can be interpreted as both a direct-dial number and a directory lookup operation, the invention provides feedback appropriate for both operations concurrently, and allows the user to select between the two operations either explicitly or by entering additional keystrokes that implicitly (but unambiguously) specify the desired operation.

In another aspect, if the user-entered series can be interpreted as both a direct-dial number and a directory lookup operation, the invention provides feedback appropriate for the directory lookup operation, but allows the user to select between the two operations either explicitly or by entering additional keystrokes that implicitly (but unambiguously) specify the desired operation. If the additional keystrokes specify that the direct-dial operation is desired, the invention deletes the displayed feedback for the directory lookup operation and provides feedback for the direct-dial operation.

In another aspect, if the user-entered series can be interpreted as both a direct-dial number and a directory lookup operation, the invention provides feedback appropriate for the direct-dial operation, but allows the user to select between the two operations either explicitly or by entering additional keystrokes that implicitly (but unambiguously) specify the desired operation. If the additional keystrokes specify that the directory lookup operation is desired, the invention deletes the displayed feedback for the direct-dial operation and provides feedback for the directory lookup operation.

If, at any point, the user-entered keystrokes unambiguously indicate the type of operation desired, the invention makes the appropriate inference, provides feedback for the desired operation, and proceeds with the desired operation.

For example, in an application where the user may dial numbers directly as well as perform directory lookup functions, the invention may operate as follows. Initially, as keystrokes are entered and both operations are possible, feedback corresponding to the directory lookup operation is displayed. If the user-entered keystroke series does not correspond to any directory record, but does correspond to a numeric sequence, the invention may infer that the user is attempting to dial a number directly. Thus, the invention may remove the directory lookup feedback and instead display feedback appropriate to a direct-dial operation.

Alternatively, as keystrokes are entered and both operations are possible, feedback corresponding to both operations may be displayed. If the user enters a keystroke that does not correspond to a numeric value, the invention may infer that the user is not attempting to dial a number directly. The invention may then remove the direct-dial feedback from the screen and proceed with the directory lookup operation. Conversely, if the user-entered keystroke series does not correspond to any directory record, but does correspond to a numeric sequence, the invention may infer that the user is attempting to dial a number directly. Thus, the invention may remove the directory lookup feedback and proceed with the direct-dial operation.

In one aspect, the invention makes the aforementioned determinations after each keystroke, so that the filtering process is iterative. As the user enters each keystroke, the invention determines which operations are still possible given the entered sequence, and adjusts the displayed feedback appropriately.

In another aspect, the invention attempts to make the aforementioned determinations after each keystroke, but if the user rapidly enters a sequence of keystrokes, the invention may wait until an appropriate pause in the sequence, or until a predetermined number of keystrokes are received, before making the aforementioned determinations.

In another aspect, the invention makes the aforementioned determinations after completion of a keystroke sequence, or when the user pauses in entering keystrokes, or when the user enters a command specifying that the determination of operation should take place.

In another aspect, the user may override the invention's determination, or may manually specify which operation is desired, or may manually specify a mode of operation. Such specification may be made before, during, or after entry of the keystrokes.

In another aspect, feedback for each of the possible operations is displayed, or is not displayed, according to user preferences, predefined settings, or other considerations. Thus, where such feedback might confuse the user, the invention may avoid such confusion.

In another aspect, directory lookup is performed concurrently with respect any of several fields, such as for example last name, first name, initials, company name, and the like. Derived fields may also be included, such as for example first initial plus last name. Combination fields may also be included, such as for example first name plus last name. The selection of which fields, derived fields, and/or combination fields are to be searched on may be predetermined or may be user-configurable, if desired. The invention filters out a record only when values in all of the specified fields fail to match the entered keystrokes. In one aspect, multiple-field directory filtering is performed concurrently with direct-dial entry, as described above, until the operation the user is attempting to perform is unambiguously determinable.

In another aspect, the user can retract a keystroke entry, for example by backspacing. The invention returns to the state that existed before the keystroke took place. Thus, if an operation is no longer valid based on a keystroke sequence, it may be reinstated if the user backspaces. Similarly, previously eliminated directory records may reappear after the user backspaces.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an oblique view of a device for practicing the present invention according to one embodiment.

FIG. 2 is a plan view of a keyboard including multiple-value keys for practicing the present invention according to one embodiment.

FIG. 3A is a flowchart depicting operation of the present invention according to one embodiment, where a directory filtering operation is initially assumed. FIG. 3B is a flowchart depicting operation of the present invention according to another embodiment, where feedback for two operations is displayed concurrently when appropriate. FIG. 3C is a flowchart depicting operation of the present invention according to one embodiment, where a direct-dial operation is initially assumed.

FIG. 4 is a block diagram depicting a functional architecture for implementing the present invention according to one embodiment.

FIG. 5 is a screen shot depicting a contacts view according to one embodiment of the present invention.

FIGS. 6A through 6E are screen shots depicting an example of a directory lookup operation according to one embodiment of the present invention, where feedback for two operations is displayed concurrently when appropriate.

FIGS. 7A through 7D are screen shots depicting an example of a direct-dial operation according to one embodiment of the present invention, where feedback for two operations is displayed concurrently when appropriate.

FIGS. 8A through 8E are screen shots depicting an example of a directory lookup operation according to one embodiment of the present invention, where a directory filtering operation is initially assumed.

FIGS. 9A through 9D are screen shots depicting an example of a direct-dial operation according to one embodi-

ment of the present invention, where a directory filtering operation is initially assumed.

The figures depict a preferred embodiment of the present invention for purposes of illustration only. One skilled in the art will readily recognize from the following discussion that alternative embodiments of the structures and methods illustrated herein may be employed without departing from the principles of the invention described herein.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

For illustrative purposes, the invention will be described in the context of a personal digital assistant (PDA) that provides functionality for direct-dialing of telephone numbers, as well as directory lookup. Accordingly, the invention is described as a mechanism for allowing the user to direct-dial a telephone number or to perform directory lookup, without first specifying which of the two operations he or she wishes to perform. In alternative embodiments, the invention provides directory filtering in multiple contexts concurrently, such as by permitting a user to filter directory records by any of a number of search criteria (including stored fields, derived fields, combination fields, and the like) without first specifying which criterion is being searched on. Such functionality may or may not be combined with direct-dial capability as well. One skilled in the art will recognize that many variations are possible, and that the particular embodiment described herein should not be considered to limit the scope of the invention in any way.

#### Device and Keyboard

Referring now to FIG. 1, there is shown PDA device **100** for practicing the present invention according to one embodiment. As is known in the art of such devices, PDA device **100** includes directory lookup and directory filtering functionality. In one embodiment, device **100** also includes cellular telephone technology for dialing, initiating, and receiving telephone calls, though such technology is not required for practicing the present invention. One skilled in the art will recognize that the present invention may be implemented in other devices or types of devices, including but not limited to: handheld, laptop, or desktop computers; cellular telephones; Internet appliances; and the like. In fact, the invention may be implemented in any device in which multiple-context searches are desired.

Device **100** includes keyboard **101** for accepting input from the user, and screen **102** for providing output and for presenting a user interface to the user. Keyboard **101** accepts alphabetic and numeric input, and further accepts commands from the user to activate various functions, scroll the display, and the like. In one embodiment, screen **102** may be a touch screen that accepts input from the user by detecting positioning of a stylus or finger. Thus, for example, a user could select a displayed record by touching screen **102** at the appropriate location. Other keystroke entry devices or character entry devices may also be employed. The use of the word "keystroke" in this patent is intended to cover any character that is entered using any input devices, and is not limited to a particular embodiment for entering character data.

Techniques for the input and output components of PDA device **100** are well known in the art. Scroll up button **104** and scroll down button **103** perform scrolling functions for navigating through on-screen data and commands.

In one embodiment, PDA device **100** runs software that controls the operation of the device including input, output, and directory lookup and filtering operations. The functionality described herein may therefore be embodied in soft-

ware that runs on PDA device **100** and that causes PDA device **100** to function in a particular manner to implement the invention. In one embodiment, the software runs in an operating system environment, such as for example the PalmOS Operating System (or a variant thereof).

Referring now to FIG. 2, there is shown an example of keyboard **101**. Keys **201** and **202** are provided for entry of alphabetic and punctuation data. Keys **201** and **202** contain multiple values, so that when a user presses one of keys **101** or **102**, a primary value (usually a letter of the alphabet) may be entered, or a secondary value (usually a number or punctuation symbol) may be entered. For example, the 'E' key has a secondary value of '\$', so that when a user presses this key, either an 'E' or a '\$' is entered. The selection of which value to enter may depend upon the context of the entry, or the field being filled, or on any other factors. Alternatively, the user may explicitly select the secondary value by 1) pressing option key **205** before pressing key **201** or **202**, or by 2) holding down option key **205** while pressing key **201** or **202**. Thus, if the user wishes to enter a '\$', he or she would press option key **205**, followed by the 'E' key. Additionally, in one embodiment, if option key **205** is pressed twice, an "option lock" mode is engaged, wherein any number of subsequent keystrokes activate their secondary values until option key **205** is pressed again to deactivate the "option lock" mode.

Shift key **206** also modifies the value entered by a keystroke. In some contexts, the user can enter an uppercase character by 1) pressing shift key **206** before pressing key **201** or **202**, or by 2) holding down shift key **206** while pressing key **201** or **202**.

Keyboard **101** also includes backspace key **203**, which deletes the most recently entered character, and enter key **204** (also referred to as return key), which indicates that the user's entry of a keystroke sequence is complete. Enter key **204** may also be used to activate a command or indicate a selection of an onscreen item, as appropriate. Space bar **207** enters a space character, or may be used to activate a command or indicate a selection, depending on the context in which it is used.

Some keys **202** contain, as one of their multiple values, a numeric value. Accordingly, a user may use keys **202** when direct-dialing a telephone number. Keys **202** are a subset of the total set of keys on keyboard **101**. In the example shown, keys **202** are denoted by a semi-oval design that distinguishes them from other keys **201**. However, one skilled in the art will recognize that any means for denoting numeric keys **202** may be employed, including but not limited to visual or tactile indicators on or near the particular keys **202**. Alternatively, if desired, such keys **102** may be given an appearance that is substantially similar to other keys **201**, with no particular indicia for distinguishing them from other keys **201**.

#### Method of Operation

In one embodiment, the present invention allows the user to dial a number or to perform directory filtering, without specifying in advance which of the two operations is intended.

In one embodiment, the invention assumes that the user is attempting to perform directory filtering, and displays directory filtering results accordingly. As long as the directory filter produces at least one result, the filter results continue to be displayed. If, however, the directory filter produces no results, and the keystroke sequence has a numeric value, then the numeric value of the keystroke sequence is displayed instead of directory filtering results. Thus, the invention switches to displaying dialed numbers if it becomes evident that the user is performing a direct-dial operation.

In another embodiment, the invention assumes that the user is attempting to perform a direct-dial operation, and displays dialed numbers. As long as the user continues to enter keystrokes that have numeric values, the numeric sequence continues to be displayed. If, however, the user enters a keystroke having no numeric value, and the keystroke sequence corresponds to a lookup string that generates filter results, then the filtered directory results are displayed instead of the numeric value of the keystroke sequence. Thus, the invention switches to displaying filtered directory results if it becomes evident that the user is performing a directory lookup operation.

In yet another embodiment, the invention concurrently displays numeric values corresponding to a dialed number, along with directory filtering results corresponding to the text values of the user's keystrokes. If the first keystroke has a numeric secondary value, that numeric value is displayed. If subsequent keystrokes also have numeric secondary values, those numeric values continue to be displayed. As long as the directory filter produces results and all entered keystrokes have numeric values, both the filter results and the numeric values continue to be displayed. If a keystroke with no numeric secondary value is entered, the numeric values disappear from the screen. If, on the other hand the directory filter produces no results, only the numeric value of the keystroke sequence is displayed.

Each of these embodiments will be described in more detail below.

Referring now to FIG. 3A, there is shown a flowchart depicting operation of the present invention according to one embodiment, where a directory filtering operation is initially assumed. Referring also to FIG. 4, there is shown a conceptual block diagram of a functional architecture for implementing the present invention according to one embodiment. One skilled in the art will recognize that the flowchart of FIG. 3A and the block diagram of FIG. 4 are merely exemplary, and that other structures and methods for implementing the invention may be used.

The user presses keys on keyboard **101** (or provides character input via some other character input device). Upon receipt of such keystroke input **301**, the invention adds **302** the value of the pressed key to a stored lookup string. In one embodiment, the lookup string may be initialized as a null string prior to step **301**. In one embodiment, step **302** and subsequent steps of FIG. 3A may be performed in response to each individual keystroke. In an alternative embodiment, the invention attempts to perform step **302** and subsequent steps of FIG. 3A in response to each keystroke, but if the user rapidly enters a sequence of keystrokes, the invention may wait until an appropriate pause in the sequence, or until a predetermined number of keystrokes are received, before proceeding with step **302** and subsequent steps of FIG. 3A. In another alternative embodiment, the invention performs step **302** and subsequent steps of FIG. 3A after completion of a keystroke sequence, or when the user pauses in entering keystrokes, or when the user enters a command specifying that the determination of operation should take place.

In one embodiment, the lookup string contains primary values of keys (such as alphabetic values, for example). In another embodiment, some coding mechanism is employed to indicate which keys are pressed, so that a coded string is formed that can later be decoded and interpreted as appropriate. If, when step **302** is to be performed, no lookup string yet exists, it may be initialized upon receipt of the first keystroke input **301**. Alternatively, a null string may be initialized before commencing the method of FIG. 3A. Once a lookup string has been established, it is stored, for

example, in buffer **401** or in any other mechanism for storing strings of data.

After the stored lookup string has been established or modified by the addition of a new keystroke value in step **302**, the invention performs a filtering operation **306** on a stored directory **403**, using the lookup string, to obtain a filtered directory set **405**. The filtering operation may be performed according to techniques that are well known in the art. For example, the invention may include, in set **405**, all directory records having a first name that begins with the lookup string. In one embodiment, the filtering operation **306** is applied to more than one field of each directory record, or to any combination of stored fields, derived fields, and/or combination fields. Thus, set **405** may include all directory records having a first name, last name, initials, or company name that begins with the lookup string. Any number of fields within directory records may be identified for matching in this manner. Thus, the invention is capable of performing a multiple-field filtering operation, in which the user may enter filtering criteria for any of a number of fields without first specifying which field is to be filtered on. The particulars of multiple-field filtering according to one embodiment are described in more detail below.

The invention determines **307** whether the filtering operation yielded any results. If the filtered set **405** is not empty, meaning that at least one directory record matches the lookup string, the filtered set **405** is displayed **308** on screen **102**. In one embodiment, as will be described in more detail below, set **405** is displayed as a scrolling list, particularly if there are more records than can fit on screen **102**. The user can navigate among the displayed records in set **405** and can select individual records for further operation, such as viewing records, modifying records, dialing numbers, and the like.

Functionality for navigating within a record set and for selecting individual records is implemented, in one embodiment, according to techniques that are well known in the art. For example, the user may navigate using scroll buttons, on-screen buttons, jog controls, and the like; the user may select records by pressing enter key **204**, or by tapping touch screen **103** at the location where the record is displayed, or by other means.

Referring momentarily to FIG. **5**, there is shown a screen shot depicting a contacts view **500** according to one embodiment of the present invention and as may be presented on screen **102**. In one embodiment, an on-screen item is highlighted **501** (for example, by displaying the item in reverse video), and the following buttons perform scrolling functions:

scroll down button **103** moves highlight **501** down one item;

scroll up button **104** moves highlight **501** up one item; holding scroll down button **103** or scroll up button **104** repeats the appropriate action at a predefined repeat rate;

scroll down button **103** preceded by shift button **206** (or while shift button **206** is held down) moves down one page;

scroll up button **104** preceded by shift button **206** (or while shift button **206** is held down) moves up one page;

holding scroll down button **103** or scroll up button **104** preceded by shift button **206** (or while shift button **206** is held down) repeats the appropriate action at a predefined repeat rate;

scroll down button **103** preceded by option button **205** (or while option button **205** is held down) moves down one category;

scroll up button **104** preceded by option button **205** (or while option button **205** is held down) moves up one category;

holding scroll down button **103** or scroll up button **104** preceded by option button **205** (or while option button **205** is held down) repeats the appropriate action at a predefined repeat rate;

space bar **207** selects the highlighted item; and enter key **204** selects the highlighted item.

In one embodiment, device **100** also includes jog rocker controls (not shown) that perform the same functions as scroll up and scroll down buttons **104** and **103**. Jog rocker control may also be pressed in to select the highlighted item

In one embodiment, the user may move highlight **501** up and down by activating on-screen scroll arrows **502** and **503**, respectively. In one embodiment, the user may select a displayed item by tapping it with a stylus or with a finger.

Once step **308** has been performed, the invention proceeds to step **309**.

If in **307** filtered set **405** is empty, meaning that no directory records match the lookup string, the invention attempts **303** to convert the lookup string to a numeric dial string **404**. In one embodiment, the conversion attempt **303** is performed by string handler **402**, which may be a software module within device **100**. Step **303** may be performed, for example, by forming a numeric sequence using secondary (numeric) values for the characters of lookup string **302**. If one or more characters do not have numeric values, the invention determines that the string cannot be converted to a numeric dial string **404**.

For example, given the keyboard **101** shown in FIG. **2**, the lookup string "HYJJJBUEHH", can be converted to the numeric string "4155557844", since each character in the lookup string corresponds to a key **202** that has a numeric secondary value. However, the lookup string "MINSTREL" cannot be converted to a numeric string, since some of the characters do not correspond to keys **202** that have a numeric secondary value.

In one embodiment, some punctuation symbols are considered permissible as part of a telephone number, and therefore are treated as having a numeric secondary value. For example, the string "JJJFMYUI" can be converted to "555-9723", and could therefore be considered a valid telephone number. Similarly, the string "SUYIDJJFYUIH" can be converted to "(213)555-1234", and could also be considered a valid telephone number. Accordingly, references to "numeric dial string" in the following descriptions can be considered to include those strings that contain punctuation or symbols that are appropriate for telephone numbers, as well as numeric characters themselves.

The invention determines **304** whether the lookup string was successfully converted to a numeric dial string **404**. If so, the invention displays **305** numeric dial string **404**, for example on display screen **102**. In one embodiment, numeric dial string **404** is displayed in a portion of screen **102** that is used for dialing in progress.

If, in **304**, the lookup string cannot be converted to a numeric dial string (for example, if the lookup string contains at least one character that does not correspond to a key **202** having a numeric secondary value), then the invention restores **316** the lookup string and display screen **102** to their previous state. Thus, the most recently entered keystroke is ignored, and display screen **102** remains unchanged. In one embodiment, the invention provides auditory feedback such as a beep, or visual feedback such as a dialog box, to inform the user that the keystroke was ignored.

In one embodiment, steps **303**, **304**, **306**, and **307** are performed by string handler **402**, which may be a software module within device **100**.

If the user enters additional character input **309**, the invention returns to step **301** to process the additional

keystrokes. If the user indicates some other command (such as selecting a displayed record, or providing a “dial” command, or selecting another operation entirely), the appropriate action is performed **314** and the method ends **315**. If appropriate, additional operations may take place. For example, if the user selects a displayed record, a directory lookup module **407** may obtain more detailed information from directory **403** for display (such as postal address, e-mail address, and the like). If the user indicates a “dial” command, either numeric dial string **404** or the telephone number associated with a selected directory record is provided to dialer **408**. Dialer **408** may be a software module for initiating a dialing operation. Telephone **409**, which may be an integrated module in device **100**, may then be activated so as to allow the user to communicate with the called party.

In one embodiment, when the user presses backspace key **203**, the most recently entered keystroke is deleted. The invention then continues with steps **306**, **307**, **308**, **303**, **304**, **316**, **305**, **309**, and **314** as described above.

Referring now to FIG. 3C, there is shown a flowchart depicting operation of the present invention according to one embodiment, where a direct-dial operation is initially assumed. One skilled in the art will recognize that the flowchart of FIG. 3C is merely exemplary, and that other methods for implementing the invention may be used.

The user presses keys on keyboard **101** (or provides character input via some other character input device). Upon receipt of such keystroke input **301**, the invention adds **302** the value of the pressed key to a stored lookup string. In one embodiment, the lookup string may be initialized as a null string prior to step **301**. In one embodiment, step **302** and subsequent steps of FIG. 3C may be performed in response to each individual keystroke. In an alternative embodiment, the invention attempts to perform step **302** and subsequent steps of FIG. 3C in response to each keystroke, but if the user rapidly enters a sequence of keystrokes, the invention may wait until an appropriate pause in the sequence, or until a predetermined number of keystrokes are received, before proceeding with step **302** and subsequent steps of FIG. 3C. In another alternative embodiment, the invention performs step **302** and subsequent steps of FIG. 3C after completion of a keystroke sequence, or when the user pauses in entering keystrokes, or when the user enters a command specifying that the determination of operation should take place.

In one embodiment, the lookup string contains primary values of keys (such as alphabetic values, for example). In another embodiment, some coding mechanism is employed to indicate which keys are pressed, so that a coded string is formed that can later be decoded and interpreted as appropriate. If, when step **302** is to be performed, no lookup string yet exists, it may be initialized upon receipt of the first keystroke input **301**. Alternatively, a null string may be initialized before commencing the method of FIG. 3C. Once a lookup string has been established, it is stored, for example, in buffer **401** or in any other mechanism for storing strings of data.

After the stored lookup string has been established or modified by the addition of a new keystroke value in step **302**, the invention attempts **303** to convert the lookup string to a numeric dial string **404**. As described above, in one embodiment, the conversion attempt **303** is performed by string handler **402**.

The invention determines **304** whether the lookup string was successfully converted to a numeric dial string **404**. If so, the invention displays **305** numeric dial string **404**, for example on display screen **102**, and proceeds to step **309**. In

one embodiment, numeric dial string **404** is displayed in a portion of screen **102** that is used for dialing in progress.

If, in **304**, the lookup string cannot be converted to a numeric dial string (for example, if the lookup string contains at least one character that does not correspond to a key **202** having a numeric secondary value), then the invention performs a filtering operation **306** on stored directory **403**, using the lookup string, to obtain a filtered directory set **405**.

The invention determines **307** whether the filtering operation yielded any results. If the filtered set **405** is not empty, meaning that at least one directory record matches the lookup string, the filtered set **405** is displayed **308** on screen **102**.

If filtered set **405** is empty, meaning that no directory records match the lookup string, the invention restores **316** the lookup string and display screen **102** to their previous state. Thus, the most recently entered keystroke is ignored, and display screen **102** remains unchanged. In one embodiment, the invention provides auditory feedback such as a beep, or visual feedback such as a dialog box, to inform the user that the keystroke was ignored.

In one embodiment, steps **303**, **304**, **306**, and **307** are performed by string handler **402**, which may be a software module within device **100**.

If the user enters additional character input **309**, the invention returns to step **301** to process the additional keystrokes. If the user indicates some other command (such as selecting a displayed record, or providing a “dial” command, or selecting another operation entirely), the appropriate action is performed **314** and the method ends **315**. If appropriate, additional operations may take place. For example, if the user selects a displayed record, a directory lookup module **407** may obtain more detailed information from directory **403** for display (such as postal address, e-mail address, and the like). If the user indicates a “dial” command, either numeric dial string **404** or the telephone number associated with a selected directory record is provided to dialer **408**. Dialer **408** may be a software module for initiating a dialing operation. Telephone **409**, which may be an integrated module in device **100**, may then be activated so as to allow the user to communicate with the called party.

In one embodiment, when the user presses backspace key **203**, the most recently entered keystroke is deleted. The invention then continues with steps **303**, **304**, **305**, **306**, **307**, **316**, **308**, **309**, and **314** as described above.

Referring now to FIG. 3B, there is shown a flowchart depicting operation of the present invention according to another embodiment, where feedback for two operations is displayed concurrently when appropriate.

The user presses keys on keyboard **101** (or provides character input via some other character input device). Upon receipt of such keystroke input **301**, the invention adds **302** the value of the pressed key to a stored lookup string. In one embodiment, the lookup string may be initialized as a null string prior to step **301**. In one embodiment, step **302** and subsequent steps of FIG. 3B may be performed in response to each individual keystroke. In an alternative embodiment, the invention attempts to perform step **302** and subsequent steps of FIG. 3B in response to each keystroke, but if the user rapidly enters a sequence of keystrokes, the invention may wait until an appropriate pause in the sequence, or until a predetermined number of keystrokes are received, before proceeding with step **302** and subsequent steps of FIG. 3B. In another alternative embodiment, the invention performs step **302** and subsequent steps of FIG. 3B after completion of a keystroke sequence, or when the user pauses in entering



keystrokes, or when the user enters a command specifying that the determination of operation should take place.

In one embodiment, the lookup string contains primary values of keys (such as alphabetic values, for example). In another embodiment, some coding mechanism is employed to indicate which keys are pressed, so that a coded string is formed that can later be decoded and interpreted as appropriate. If, when step **302** is to be performed, no lookup string yet exists, it may be initialized upon receipt of the first keystroke input **301**. Alternatively, a null string may be initialized before commencing the method of FIG. **3B**. Once a lookup string has been established, it is stored, for example, in buffer **401** or in any other mechanism for storing strings of data.

After the stored lookup string has been established or modified by the addition of a new keystroke value in step **302**, the invention attempts **303** to convert the lookup string to a numeric dial string **404**.

The invention determines **304** whether the lookup string was successfully converted to a numeric dial string **404**. If so, the invention displays **305** numeric dial string **404**, for example on display screen **102**. In one embodiment, numeric dial string **404** is displayed in a portion of screen **102** that is used for dialing in progress. As will be described in more detail below, a user interface may be provided which contains such a screen portion for providing dialing feedback, while another screen portion is concurrently used for directory lookup feedback. Thus, the user can perform either a direct-dial operation or a directory filtering operation, and receive appropriate feedback for the operation being performed, without having to specify in advance which operation is desired.

If, in **304**, the lookup string cannot be converted to a numeric dial string (for example, if the lookup string contains at least one character that does not correspond to a key **202** having a numeric secondary value), then no numeric dial string is displayed. In one embodiment, the corresponding portion of screen **102** is left blank, and any previously displayed numeric dial string is deleted; in another embodiment, an indicator is displayed to inform the user that the direct-dial operation is no longer active. Auditory or other feedback may also be provided to indicate that direct-dial is no longer active.

The invention performs a filtering operation **306** on a stored directory **403**, using the lookup string, to obtain a filtered directory set **405**.

The invention determines **307** whether the filtering operation yielded any results. If the filtered set **405** is not empty, meaning that at least one directory record matches the lookup string, the filtered set **405** is displayed **308** on screen **102**.

If filtered set **405** is empty, meaning that no directory records match the lookup string, the invention may leave the corresponding area of screen **102** blank, or may display feedback indicating that no records match. Auditory or other feedback may also be provided to indicate that no records match. In one embodiment, auditory or other feedback may be provided when direct-dial is not active (because at least one entered keystroke has no numeric secondary value) and no records match the lookup string. The user is thereby notified that his or her keystroke entry has thus far yielded no valid results according to either direct-dialing or directory filtering. The user may thereby be encouraged to backspace space so as to delete the most recently typed keystroke, as described below.

In one embodiment, steps **303**, **304**, **306**, and **307** are performed by string handler **402**, which may be a software module within device **100**.

If the user enters additional character input **309**, the invention returns to step **301** to process the additional keystrokes. If the user indicates some other command (such as selecting a displayed record, or providing a "dial" command, or selecting another operation entirely), the appropriate action is performed **314** and the method ends **315**. If appropriate, additional operations may take place. For example, if the user selects a displayed record, a directory lookup module **407** may obtain more detailed information from directory **403** for display (such as postal address, e-mail address, and the like). If the user indicates a "dial" command, either numeric dial string **404** or the telephone number associated with a selected directory record is provided to dialer **408**. Dialer **408** may be a software module for initiating a dialing operation. Telephone **409**, which may be an integrated module in device **100**, may then be activated so as to allow the user to communicate with the called party.

In one embodiment, when the user presses backspace key **203**, the most recently entered keystroke is deleted. The invention then continues with steps **303** through **314** as described above. Since pressing backspace key **203** shortens the lookup string, in general such an action may enlarge the filtered set, and/or may reactivate the direct-dial operation where it may previously have been rendered inactive by entry of a keystroke having no numeric secondary value. In other words, the user may delete those keystrokes that have no numeric secondary value and thereby reactivate the direct-dial operation.

Thus, the present invention allows a user to enter keystrokes corresponding to a direct-dial operation, or corresponding to a directory filtering operation, where some or all of the keystrokes correspond to multiple-value keys, without having to specify which operation is intended. The invention determines which operation is intended based on whether the user enters any non-numeric keystrokes and/or on whether the directory, when filtered according to the entered keystrokes, yields any records. As described above, the invention makes the aforementioned determinations after each keystroke, or after a series of keystrokes, so that the filtering process is iterative.

In one embodiment, the user may override the invention's determination, or may manually specify which operation is desired, or may manually specify a mode of operation. Such specification may be made before, during, or after entry of the keystrokes. The for example, the user might be given the opportunity to specify that a direct-dial operation is intended by tapping screen **102** in a location where the direct-dial number is displayed. Thereafter, during the current direct-dial operation, subsequent keystrokes are interpreted as numeric. If a key having no numeric secondary value is pressed, the invention may ignore the keystroke or may provide auditory or other feedback to indicate that the keystroke is not accepted.

In one embodiment, the user may enter numeric characters as part of the lookup string (for example, if the company name contains a numeric character, such as "3Com"). A "num-lock" mode may be provided, as is known in the art, for entering numeric characters in this manner. The user may enter such a mode by pressing option key **205** before pressing key **202** having a numeric secondary value. The numeric value (rather than the alphabetic value) of the pressed key **202** will then be added to the lookup string. In another embodiment, the invention performs the filtering operation using all possible combinations of primary and secondary values for lookup string keystrokes. Thus, a lookup string of "ICOM" would match directory entries

having relevant fields containing "ICOM", "3COM", "ICO9", and any other combination of primary and secondary values for the entered keystrokes.

In an alternative embodiment, keys may be associated with other values besides the primary and secondary values. For example, the "E" key may be associated with other values similar to or related to "E", such as "e", "e" and "e". Individual characters in the lookup string are considered to match these other values. Thus, a lookup string of "BET" would match "B ê te". The other values may or may not appear on the keyboard itself. In addition, the other values may be associated with keys **201** having non-numeric secondary values, keys **202** having numeric secondary values, and/or keys having no secondary values (not shown).

In an alternative embodiment, in performing the directory filter step **306**, in addition to identifying directory records having fields that match the lookup string, the invention also identifies directory records having a telephone number that matches numeric dial string **404** (if such a string is valid and available). Thus, filtered directory set **405** includes records that contain matching telephone numbers as well as matching names (or other fields). The user can thereby enter the first few digits of a telephone number and, if the corresponding directory record exists within directory **403**, the user may select the desired record from a displayed list of records having a telephone number that matches the entered digits. The user can select the desired record and dial the associated number without having to enter the rest of the number.

In another embodiment, if filtered directory set **405** is reduced to one record, the invention may automatically select that record for retrieval, or for dialing, or for some other operation. Alternatively, the user interface of the invention may provide an "auto-fill" function whereby the remainder of the name (or other field) is automatically filled in on behalf of the user, once a particular record can be identified from the user's input. Techniques of "auto-filling" in this manner are well known in the art.

In one embodiment, the user may override the invention's determination as to whether a directory filtering operation or a direct-dial operation is intended. The invention may provide a preference screen for selecting which operation is active. Alternatively, a command may be available for manually specifying which operation is intended, or which mode of operation is desired. Such specification may be made before, during, or after entry of the keystrokes.

In one embodiment, feedback for each of the possible operations is displayed, or is not displayed, according to user preferences or other considerations. Thus, where such feedback might confuse the user, the invention may avoid such confusion. For example, the user may specify in a preference screen that dial strings are to be displayed in a different color, style, or font than directory filter results. One skilled in the art will recognize that other options for configuring or personalizing the operation of the invention may be contemplated.

#### Multiple-Field Filtering

In one embodiment, the invention filters directory records concurrently based on multiple fields. With each keystroke, all non-matching records are filtered out, and matches are displayed (although if there are more matches than can fit on screen **102**, scrolling is enabled to allow navigation among matching records). The lookup string is applied to several fields concurrently, so that the filter results include all records for which any of the several fields matches the lookup string. Particular fields may be designated as searchable, so that the lookup string is applied to those fields but not other fields. Field combinations and/or derived fields

may also be designated, such as for example: first initial plus last name (a derived field), or first name plus last name (a field combination). Derived fields are fields that can be generated by performing an operation on one or more other fields. Combination fields are fields that can be generated by combining two or more other fields. Derived fields and combination fields need not be stored in directory **403**, but may be generated "on the fly" as needed. One skilled in the art will recognize that the invention may perform searches on any combination of stored fields, derived fields, combination fields, and the like.

In one embodiment, the invention filters the lookup string against the following fields:

first name (for example, lookup string "GR" would match "Greg Shirai");

last name (for example, lookup string "GR" would also match "Bob Green");

derived field: first initial and last initial (for example, lookup string "GR" would also match "Gus Rollins");

derived field: first initial and last name (for example, lookup string "GRA" would match "Gary Randolph");

field combination: first name and last name if a space is entered between them (for example, lookup string "GR RA", which includes a space after the second character, would match "Greg Ralston"); and

company name.

One skilled in the art will recognize that other fields, field combinations, or derived fields could also be used.

In addition, as discussed above, characters within the lookup string may match similar or related values in directory record fields. Thus, for example, lookup string "RBE" would match "Robert B ê te", since the "E" matches the "ê".

In one embodiment, spaces (or other punctuation) within a name are ignored, for pattern matching purposes. Thus, "TVONBR" would match "Tom von Bridgwater", where "von" is part of the last name and not a middle name. Similarly, "ELM" would match "Jane El-Makim", since the hyphen would be ignored. "EL-M" would also match "Jane El-Makim", should the user elect to include the hyphen in the lookup string.

As described above, if the user backspaces so as to delete the last character, the filter results revert to those shown before the last character was entered.

In one embodiment of the invention, multiple-field filtering is provided without automatically determining whether the user intends a directory filter or direct-dial operation. In another embodiment, multiple-field filtering is combined with automatic determination as to whether the user intends a directory filter or direct-dial operation.

#### Examples of User Interface

Referring now to FIGS. **8A** through **8E**, there are shown screen shots depicting an example of a directory filtering operation according to one embodiment of the present invention where a directory filtering operation is initially assumed. The screen shots of FIGS. **8A** through **8E** correspond to the method described above in connection with FIG. **3A**. In the example shown, the user is attempting to look up John Birch's number in the directory in order to call him on his work telephone number.

Referring now to FIG. **8A**, initial contact screen **800** is shown. Screen **800** may be activated, for example, by simply turning on device **100**, or by entering a mode for directory lookup, or by activating a phone application. Screen **800** includes a number of contact records **601**, scroll arrows **502** and **503** for navigating to additional records, and on-screen controls **602** for activating other functions of device **100**.

In one embodiment, screen **800** may be skipped entirely, so that the invention proceeds directly to screen **810**, depicted in FIG. **8B**, in response to the user entering a keystroke.

Since the user is attempting to look up "Birch, John", he or she first presses the "B" key. At this point, screen **810** is displayed, as depicted in FIG. **8B**. Screen **810** shows the results of a filtering operation on the directory using the letter "B", and therefore includes records from the directory that begin with the letter "B". Additional records that begin with "B" may be available, and may be accessed by scrolling. The filter is applied to multiple fields, so that the displayed records include those having a first name beginning with "B" (Biff Henderson), as well as those having a last name beginning with "B" (John Birch, C J Bush). In one embodiment, records having a company name, or initials, or other relevant field that begins with "B" would also be displayed. The first telephone number in the first displayed record is selected (as indicated by highlight **604**), although in alternative embodiments a different record might be selected.

Screen **810** also includes lookup string field **605** that displays the lookup string, consisting of the characters entered thus far. Accordingly, a "b" is currently displayed, indicating that the user has entered the letter "B". As the user enters additional characters, field **605** helps to remind the user of the criteria on which the directory is being filtered, and also reduces user confusion when he or she backspaces and types additional characters. One skilled in the art will recognize that lookup string field **605** is not required, and the set of displayed contact records **601** may offer sufficient feedback to the user. Accordingly, in an alternative embodiment, lookup string field **605** is not displayed, or the display of lookup string field **605** is configurable by the user.

Still attempting to zero in on "Birch, John", the user now presses the "I" key. At this point, screen **820** is displayed, as depicted in FIG. **8C**. Screen **820** shows the results of the filtering operation on the directory using the lookup string "BI", and therefore now includes records that begin with "BI". Again, additional records that begin with "BI" may be accessible via scrolling. Now, two records are displayed: Biff Henderson (since the first name begins with "BI") and John Birch (since the last name begins with "BI"). Lookup string field **605** now shows "bi".

Next, the user presses the "R" key. At this point, screen **630** is displayed, as depicted in FIG. **8D**. Screen **630** shows the results of the filtering operation on the directory using the lookup string "BIR", and therefore now includes records that begin with "BIR". Again, additional records that begin with "BIR" may be accessible via scrolling. However, in the example shown, only one record matches the filter: John Birch. Thus, John Birch's first listed telephone number is now highlighted **601**. Lookup string field **605** now shows "bir".

Now that the user has successfully pinpointed the record he or she was interested in, he or she presses space bar **207** or enter key **204** to dial the highlighted number **601**. Alternatively, the user may tap the number on the screen (with a stylus or finger), or may press a jog rocker control (not shown).

Referring now to FIG. **8E**, there is shown screen **640**, which contain various user interface elements that are relevant to a call in progress. The name and number of the called party are displayed **641**, as well as an indication that the call is active **644** and a call timer **642**. Additional controls **643** are provided, for operations such as hang up, hold, extra digits, or keypad.

Referring now to FIGS. **9A** through **9D**, there are shown screen shots depicting an example of a direct-dial operation according to one embodiment of the present invention, where a directory filtering operation is initially assumed.

The screen shots of FIGS **9A** through **9D** correspond to the method described above in connection with FIG. **3A**. In the example shown, the user is attempting to dial the number 730-788-5457.

Since the user is attempting to dial 730-788-5457 he or she first presses the key having a numeric secondary value of "7". At this point, screen **900** is displayed, as depicted in FIG. **9A**. Since the primary value of the "7" key is the letter "B", screen **900** shows the results of a filtering operation on the directory using the letter "B", including records from the directory that begin with the letter "B". Additional records that begin with "B" may be available, and may be accessed by scrolling. The filter is applied to multiple fields, so that the displayed records include those having a first name beginning with "B" (Biff Henderson), as well as those having a last name beginning with "B" (John Birch, C J Bush). In one embodiment, records having a company name, or initials, or other relevant field that begins with "B" would also be displayed. The first telephone number in the first displayed record is selected (as indicated by highlight **604**), although in alternative embodiments other records might be selected. Screen **900** also includes lookup string field **605** that displays the lookup string, consisting of the primary values for the keystrokes entered thus far. Accordingly, a "b" is currently displayed, indicating that the user has entered the letter "B". Again, in an alternative embodiment, lookup string field **605** is not displayed, or the display of lookup string field **605** is configurable by the user.

At this point the invention cannot determine whether the user is attempting to look up a directory record or direct-dialing a telephone number. In fact, the behavior of the user at this point is identical to the behavior of the user in the previous example prior to the display of screen **810**, since in both cases the "B" key (having a secondary value of "7") was pressed. Thus, screen **900** is identical to screen **810**.

Continuing to dial the number, the user presses the key having a numeric secondary value of "3". At this point, screen **901** is displayed, as depicted in FIG. **9B**.

Since the primary value of the "3" key is the letter "I", screen **900** shows the results of a filtering operation on the directory using the lookup string "BI", including records from the directory that begin with the letters "BI". Again, additional records that begin with "BI" may be accessible via scrolling. Now, two records are displayed: Biff Henderson (since the first name begins with "BI") and John Birch (since the last name begins with "BI"). Lookup string field **605** now shows "bi".

Since the invention still cannot determine whether the user is performing directory lookup or direct-dial, feedback appropriate to directory lookup is still displayed. In fact, the behavior of the user at this point is identical to the behavior of the user in the previous example prior to the display of screen **820**, since in both cases the "B" key and the "I" key (having secondary values of "7" and "3", respectively) were pressed. Thus, screen **901** is identical to screen **820**.

Next, the user presses the key having a numeric secondary value of "0". At this point, screen **920** is displayed, as depicted in FIG. **9C**. Dial string **611** is now displayed, and now reads "730", corresponding to the numeric values of the three keys thus far entered. Directory filtering feedback is no longer displayed.

The primary value of the "0" key is a symbol, which has special meaning when entering text. It is used for accessing special symbols that are not displayed on the keyboard. No records in the database begin with the string "BI" followed by a special symbol. Thus, the filtering operation on this lookup string yields no results, and no records are now

displayed. The invention can now infer that the user is direct-dialing a number, since all the entered keystrokes have numeric values and the lookup string yields no results. Accordingly, dial string **611** is now highlighted to indicate that it is the only valid operation. However, if the user were to now press backspace key **203** at this point, deleting the “0”, the lookup string would revert to “BI” and screen **901** would again be displayed.

At this point, the user simply enters the remaining digits in the number being dialed. Referring now to FIG. 9D, there is shown display screen **930** after the user has completed entry of a ten-digit telephone number. Hyphens in dial string **611** may be added automatically, according to standard telephone number syntax. Once the user has finished entering the number, he or she presses space bar **207** or enter key **204** to dial the number. Alternatively, the user may tap the number on the screen (with a stylus or finger), or may press a jog rocker control (not shown).

In one embodiment, once the invention has reached a state where no records match the lookup string (e.g. screen **920**), non-numeric keystrokes are rejected. Thus, if the user presses a key that does not have a numeric value, the invention may ignore the keystroke, or may provide feedback (such as a beep, for example) indicating that the entry is invalid.

Referring now to FIGS. 6A through 6E, there are shown screen shots depicting an example of a directory filtering operation according to one embodiment of the present invention, where feedback for two operations is displayed concurrently when appropriate. The screen shots of FIGS. 6A through 6E correspond to the method described above in connection with FIG. 3B. In the example shown, the user is attempting to look up John Birch’s number in the directory in order to call him on his work telephone number.

Referring now to FIG. 6A, initial contact screen **600** is shown. Screen **600** may be activated, for example, by simply turning on device **100**, or by entering a mode for directory lookup, or by activating a phone application. Screen **600** includes a number of contact records **601**, scroll arrows **502** and **503** for navigating to additional records, and on-screen controls **602** for activating other functions of device **100**.

In one embodiment, screen **600** may be skipped entirely, so that the invention proceeds directly to screen **610**, depicted in FIG. 6B, in response to the user entering a keystroke.

Since the user is attempting to look up “Birch, John”, he or she first presses the “B” key. At this point, screen **610** is displayed, as depicted in FIG. 6B. Screen **610** shows the results of a filtering operation on the directory using the letter “B”, and therefore includes records from the directory that begin with the letter “B”. Additional records that begin with “B” may be available, and may be accessed by scrolling. The filter is applied to multiple fields, so that the displayed records include those having a first name beginning with “B” (Biff Henderson), as well as those having a last name beginning with “B” (John Birch, C J Bush). In one embodiment, records having a company name, or initials, or other relevant field that begins with “B” would also be displayed. The first telephone number in the first displayed record is selected (as indicated by highlight **604**), although in alternative embodiments a different record might be selected.

Screen **610** also includes lookup string field **605** that displays the lookup string, consisting of the characters entered thus far. Accordingly, a “b” is currently displayed, indicating that the user has entered the letter “B”. As the user enters additional characters, field **605** helps to remind the

user of the criteria on which the directory is being filtered, and also reduces user confusion when he or she backspaces and types additional characters. Again, in an alternative embodiment, lookup string field **605** is not displayed, or the display of lookup string field **605** is configurable by the user.

Screen **610** also displays dial string **611**. The “B” key has a numeric secondary value of “7”. Thus, at this point the invention cannot determine whether the user is attempting to look up a directory record or direct-dialing a telephone number. Accordingly, in addition to displaying filtered directory records, screen **610** also displays the number “7” as part of dial string **611**. If the user is in fact direct-dialing a number, he or she will regard the display of dial string **611** as feedback in response to his or her keystrokes. Conversely, if the user is attempting directory lookup, he or she will regard lookup string field **605**, along with the filtered result records **601**, as feedback in response to keystrokes. By providing both forms of feedback concurrently, the invention allows the user to proceed with assurance that his or her actions are being correctly interpreted, despite the fact that neither of the two modes (directory lookup or direct-dial) has been explicitly specified.

In one embodiment, dial string **611** is displayed in a different font or visual style than is used for directory records, so as to indicate to the user that dial string **611** is not representative of a matching record.

Still attempting to zero in on “Birch, John”, the user now presses the “I” key. At this point, screen **620** is displayed, as depicted in FIG. 6C. Screen **620** shows the results of the filtering operation on the directory using the lookup string “BI”, and therefore now includes records that begin with “BI”. Again, additional records that begin with “BI” may be accessible via scrolling. Now, two records are displayed. Biff Henderson (since the first name begins with “BI”) and John Birch (since the last name begins with “BI”). Lookup string field **605** now shows “bi”. Dial string **611** is displayed as well, and now reads “73”, since the “I” key has a numeric secondary value of “3”. Since the invention still cannot determine whether the user is performing directory lookup or direct-dial, both forms of feedback are still displayed.

Next, the user presses the “R” key. At this point, screen **630** is displayed, as depicted in FIG. 6D. Screen **630** shows the results of the filtering operation on the directory using the lookup string “BIR”, and therefore now includes records that begin with “BIR”. Again, additional records that begin with “BIR” may be accessible via scrolling. However, in the example shown, only one record matches the filter: John Birch. Thus, John Birch’s first listed telephone number is now highlighted **601**. Lookup string field **605** now shows “bir”. Since the “R” key does not have a numeric secondary value, the invention can now infer that the user is not direct-dialing a number, and therefore dial string **611** is no longer displayed. However, if the user were to now press backspace key **203**, deleting the “R”, the state of the display would revert to screen **620**, depicted in FIG. 6C.

Now that the user has successfully pinpointed the record he or she was interested in, he or she presses space bar **207** or enter key **204** to dial the highlighted number **601**. Alternatively, the user may tap the number on the screen (with a stylus or finger), or may press a jog rocker control (not shown).

Referring now to FIG. 6E, there is shown screen **640**, which contain various user interface elements that are relevant to a call in progress. The name and number of the called party are displayed **641**, as well as an indication that the call is active **644** and a call timer **642**. Additional controls **643** are provided, for operations such as hang up, hold, extra digits, or keypad.

Referring now to FIGS. 7A through 7D, there are shown screen shots depicting an example of a direct-dial operation according to one embodiment of the present invention, where feedback for two operations is displayed concurrently when appropriate. The screen shots of FIGS. 7A through 7D correspond to the method described above in connection with FIG. 3B. In the example shown, the user is attempting to dial the number 730-788-5457.

Since the user is attempting to dial 730-788-5457 he or she first presses the key having a numeric secondary value of "7". At this point, screen 700 is displayed, as depicted in FIG. 7A. Screen 700 displays dial string 611 containing the numeric value of the entered key, which is "7".

Since the primary value of the "7" key is the letter "B", screen 700 also shows the results of a filtering operation on the directory using the letter "B", including records from the directory that begin with the letter "B". Additional records that begin with "B" may be available, and may be accessed by scrolling. The filter is applied to multiple fields, so that the displayed records include those having a first name beginning with "B" (Biff Henderson), as well as those having a last name beginning with "B" (John Birch, C J Bush). In one embodiment, records having a company name, or initials, or other relevant field that begins with "B" would also be displayed. The first telephone number in the first displayed record is selected (as indicated by highlight 604), although in alternative embodiments other records might be selected. Screen 700 also includes lookup string field 605 that displays the lookup string, consisting of the primary values for the keystrokes entered thus far. Accordingly, a "b" is currently displayed, indicating that the user has entered the letter "B". Again, in an alternative embodiment, lookup string field 605 is not displayed, or the display of lookup string field 605 is configurable by the user.

At this point the invention cannot determine whether the user is attempting to look up a directory record or direct-dialing a telephone number. In fact, the behavior of the user at this point is identical to the behavior of the user in the previous example prior to the display of screen 610, since in both cases the "B" key (having a secondary value of "7") was pressed. Thus, screen 700 is identical to screen 610.

Continuing to dial the number, the user presses the key having a numeric secondary value of "3". At this point, screen 701 is displayed, as depicted in FIG. 7B. Dial string 611 is displayed, and now reads "73", corresponding to the numeric values of the two keys thus far entered.

Since the primary value of the "3" key is the letter "I", screen 700 also shows the results of a filtering operation on the directory using the lookup string "BI", including records from the directory that begin with the letters "BI". Again, additional records that begin with "BI" may be accessible via scrolling. Now, two records are displayed: Biff Henderson (since the first name begins with "BI") and John Birch (since the last name begins with "BI"). Lookup string field 605 now shows "bi".

Since the invention still cannot determine whether the user is performing directory lookup or direct-dial, both forms of feedback are still displayed. In fact, the behavior of the user at this point is identical to the behavior of the user in the previous example prior to the display of screen 620, since in both cases the "B" key and the "I" key (having secondary values of "7" and "3", respectively) were pressed. Thus, screen 701 is identical to screen 620.

Next, the user presses the key having a numeric secondary value of "0". At this point, screen 720 is displayed, as depicted in FIG. 7C. Dial string 611 is displayed, and now reads "730", corresponding to the numeric values of the three keys thus far entered.

The primary value of the "0" key is a symbol, which has special meaning when entering text. It is used for accessing special symbols that are not displayed on the keyboard. No records in the database begin with the string "BI" followed by a special symbol. Thus, the filtering operation on this lookup string yields no results, and no records are now displayed. The invention can now infer that the user is direct-dialing a number, since all the entered keystrokes have numeric values and the lookup string yields no results. Accordingly, dial string 611 is now highlighted to indicate that it is the only valid operation. However, if the user were to now press backspace key 203 at this point, deleting the "0", the lookup string would revert to "BI" and screen 701 would again be displayed.

At this point, the user simply enters the remaining digits in the number being dialed. Referring now to FIG. 7D, there is shown display screen 730 after the user has completed entry of a ten-digit telephone number. Hyphens in dial string 611 may be added automatically, according to standard telephone number syntax. Once the user has finished entering the number, he or she presses space bar 207 or enter key 204 to dial the number. Alternatively, the user may tap the number on the screen (with a stylus or finger), or may press a jog rocker control (not shown).

In one embodiment, once the invention has reached a state where no records match the lookup string (e.g. screen 720), non-numeric keystrokes are rejected. Thus, if the user presses a key that does not have a numeric value, the invention may ignore the keystroke, or may provide feedback (such as a beep, for example) indicating that the entry is invalid.

As can be seen from the above description and examples, the present invention allows the user to perform a directory filtering operation or to direct-dial a number, on a keyboard having multiple-value keys, without first specifying which operation is intended. The invention further provides functionality for filtering on multiple fields in a directory, including derived fields and/or combination fields. As will be understood by those familiar with the art, the invention may be embodied in other specific forms without departing from the spirit or essential characteristics thereof. For example, the particular architectures depicted above are merely exemplary of one implementation of the present invention. The functional elements, method steps, screen shots, and user interface elements described above are provided as illustrative examples of one technique for implementing the invention; one skilled in the art will recognize that many other implementations are possible without departing from the present invention as recited in the claims. Likewise, the particular capitalization or naming of the modules, protocols, features, attributes, or any other aspect is not mandatory or significant, and the mechanisms that implement the invention or its features may have different names or formats. Accordingly, the disclosure of the present invention is intended to be illustrative, but not limiting, of the scope of the invention, which is set forth in the following claims.

What is claimed is:

1. A computer-implemented method for concurrently accepting parameters in at least two contexts, the method comprising:

- accepting a keystroke sequence comprising at least one keystroke, each keystroke having a first value, and at least one keystroke having a second value;
- determining whether the keystroke sequence produces a valid result in a first context;
- responsive to the keystroke sequence producing a valid result in the first context:

23

outputting first feedback, the first feedback indicating keystroke input according to the first context; and performing a first action corresponding to the first context, using the first value for each keystroke;

responsive to the keystroke sequence not producing a valid result in the first context:

determining whether the keystroke sequence produces a valid result in a second context; and

responsive to the keystroke sequence producing a valid result in the second context:

outputting second feedback, the second feedback indicating keystroke input according to the second context; and

performing a second action corresponding to the second context, using the second value for each keystroke.

2. The method of claim 1, wherein:

the first feedback indicates the first value for each keystroke; and

the second feedback indicates the second value for each keystroke.

3. The method of claim 1, wherein the first feedback comprises visual feedback and the second feedback comprises visual feedback.

4. The method of claim 1, further comprising:

responsive to the keystroke sequence not producing a valid result in the first context and in the second context, outputting an invalidity indicator.

5. The method of claim 4, wherein outputting an invalidity indicator comprises outputting an auditory invalidity indicator.

6. The method of claim 4, wherein outputting an invalidity indicator comprises outputting a visual invalidity indicator.

7. The method of claim 1, wherein at least one of the contexts comprises accepting input for a directory filtering operation on a plurality of directory records.

8. The method of claim 7, wherein the first context comprises accepting input for a directory filtering operation on a plurality of directory records.

9. The method of claim 8, wherein the directory filtering operation is iterative.

10. The method of claim 8, further comprising:

responsive to the keystroke sequence producing a valid result in the first context, performing the directory filtering operation using the first value for each of the accepted keystrokes.

11. The method of claim 8, further comprising:

responsive to the keystroke sequence producing a valid result in the first context, performing the directory filtering operation using the accepted keystrokes;

wherein determining whether the keystroke sequence produces a valid result in a first context comprises determining whether the performed directory filtering operation produces at least one valid result for the keystroke sequence.

12. The method of claim 8, further comprising:

responsive to the keystroke sequence producing a valid result in the first context, performing the directory filtering operation using the accepted keystrokes;

wherein each directory record comprises contents, and wherein performing the directory filtering operation comprises comparing the keystroke sequence with the contents of at least one directory record.

13. The method of claim 12, wherein the first feedback comprises at least one matching directory record.

24

14. The method of claim 8, further comprising:

responsive to the keystroke sequence producing a valid result in the first context, performing the directory filtering operation using the accepted keystrokes;

wherein each directory record comprises at least one field value, and wherein the directory filtering operation comprises comparing the keystroke sequence with at least one field value in at least one directory record.

15. The method of claim 14, wherein the first feedback comprises at least one matching directory record.

16. The method of claim 8, further comprising:

responsive to the keystroke sequence producing a valid result in the first context, performing the directory filtering operation using the accepted keystrokes;

wherein the directory filtering operation comprises comparing the keystroke sequence with at least two field values in at least one directory record.

17. The method of claim 8, further comprising:

responsive to the keystroke sequence producing a valid result in the first context, performing the directory filtering operation using the accepted keystrokes;

wherein each directory record comprises at least two field values, and wherein the directory filtering operation comprises comparing the keystroke sequences with at least one value derived from at least one field in at least one directory record.

18. The method of claim 8, further comprising:

responsive to the keystroke sequence producing a valid result in the first context, performing the directory filtering operation using the accepted keystrokes;

wherein each directory record comprises at least two field values, and wherein the directory filtering operation comprises comparing the keystroke sequences with at least one field value in at least one directory record and with at least one value derived from at least one field in at least one directory record.

19. The method of claim 8, wherein the first feedback comprises at least one matching directory record.

20. The method of claim 1, further comprising:

accepting an additional keystroke, the additional keystroke having at least a first value;

appending the additional keystroke to the keystroke sequence;

repeating the steps of:

determining whether the keystroke sequence produces a valid result in a first context;

responsive to the keystroke sequence producing a valid result in the first context, outputting first feedback, the first feedback indicating keystroke input according to the first context;

responsive to the keystroke sequence not producing a valid result in the first context:

determining whether the keystroke sequence produces a valid result in a second context; and

responsive to the keystroke sequence producing a valid result in the second context, outputting second feedback, the second feedback indicating keystroke input according to the second context.

21. The method of claim 1, further comprising:

accepting a backspace keystroke;

deleting a keystroke from the keystroke sequence;

repeating the steps of:

determining whether the keystroke sequence produces a valid result in a first context;

25

responsive to the keystroke sequence producing a valid result in the first context, outputting first feedback, the first feedback indicating keystroke input according to the first context; and

responsive to the keystroke sequence not producing a valid result in the first context:

determining whether the keystroke sequence produces a valid result in a second context; and

responsive to the keystroke sequence producing a valid result in the second context, outputting second feedback, the second feedback indicating keystroke input according to the second context.

22. The method of claim 1, wherein at least one of the contexts comprises accepting input for a direct entry operation.

23. The method of claim 22, wherein the first context comprises accepting input for a direct entry operation.

24. The method of claim 23, wherein the direct entry operation comprises a telephone number direct entry operation.

25. The method of claim 23, wherein determining whether the keystroke sequence produces a valid result in a first context comprises determining whether all of the accepted keystrokes have a numeric value.

26. The method of claim 23, further comprising:

responsive to the keystroke sequence producing a valid result in the first context, performing the direct entry operation using the first value for each of the accepted keystrokes.

27. The method of claim 23, further comprising:

responsive to the keystroke sequence producing a valid result in the first context, performing the direct entry operation using the accepted keystrokes.

28. The method of claim 1, wherein the first context comprises accepting input for a directory filtering operation, and the second context comprises accepting input for a direct entry operation.

29. The method of claim 28, further comprising:

responsive to the keystroke sequence producing a valid result in the first context, performing the directory filtering operation using the first value for each of the accepted keystrokes; and

responsive to the keystroke sequence not producing a valid result in the first context and producing a valid result in the second context, performing the direct entry operation using the second value for each of the accepted keystrokes.

30. The method of claim 29, wherein:

determining whether the keystroke sequence produces a valid result in a first context comprises determining whether the performed directory filtering operation produces at least one valid result for the accepted keystrokes; and

determining whether the keystroke sequence produces a valid result in a second context comprises determining whether all of the accepted keystrokes have a numeric value.

31. The method of claim 1, wherein:

each first value comprises one selected from the group consisting of a letter and a punctuation symbol; and each second value comprises a number.

32. The method of claim 1, wherein:

each first value comprises one selected from the group consisting of a letter and a punctuation symbol; and each second value comprises one selected from the group consisting of a number and a punctuation symbol.

26

33. The method of claim 1, further comprising:

responsive to at least one of the accepted keystrokes not being valid in one of the contexts, determining that the other context is intended.

34. The method of claim 1, further comprising:

responsive to the keystroke sequence not producing a valid result in one of the contexts, performing an action using the keystroke sequence according to the other context.

35. The method of claim 1, wherein accepting a keystroke sequence comprises accepting a keystroke sequence entered via a QWERTY keyboard having a plurality of keys, wherein a subset of the keys have secondary numeric values.

36. The method of claim 35, wherein the subset of the keys having secondary numeric values are arranged according to a numeric keypad layout.

37. A computer-implemented method for concurrently accepting parameters in at least two contexts, the method comprising:

accepting a keystroke sequence comprising at least one keystroke, each keystroke having a first value, and at least one keystroke having a second value;

determining whether the keystroke sequence produces a valid result in a first context;

responsive to the keystroke sequence producing a valid result in the first context:

outputting first feedback, the first feedback indicating keystroke input according to the first context; and performing a first action corresponding to the first context, using the first value for each keystroke;

responsive to the keystroke sequence not producing a valid result in the first context:

determining whether the keystroke sequence produces a valid result in a second context; and

responsive to the keystroke sequence producing a valid result in the second context:

outputting second feedback, the second feedback indicating keystroke input according to the second context; and

performing a second action corresponding to the second context, using the second value for each keystroke.

38. The method of claim 37, wherein:

the first feedback indicates the first value for each keystroke; and

the second feedback indicates the second value for each keystroke.

39. The method of claim 37, further comprising:

responsive to at least one of the accepted keystrokes being invalid in one of the contexts, deleting feedback indicating keystroke input according to said one of the contexts.

40. The method of claim 37, wherein the first feedback comprises visual feedback and the second feedback comprises visual feedback.

41. The method of claim 40, wherein:

outputting the first visual feedback comprises outputting the first visual feedback at a first location on a display screen; and

outputting the second visual feedback comprises outputting the second visual feedback at a second location on a display screen.

42. The method of claim 37, wherein the first context comprises accepting input for a directory filtering operation on a plurality of directory records.

27

43. The method of claim 42, wherein the directory filtering operation is iterative.

44. The method of claim 37, further comprising:

accepting an additional keystroke, the additional keystroke having at least a first value;

appending the additional keystroke to the keystroke sequence;

repeating the steps of determining whether the keystroke sequence produces a valid result in a first context, and responsive to the key-stroke sequence producing a valid result in the first context, outputting first feedback, the first feedback indicating keystroke input according to the first context; and

repeating the steps of responsive to the keystroke sequence not producing a valid result in the first context, determining whether the keystroke sequence produces a valid result in a second context, and, responsive to the keystroke sequence producing a valid result in the second context, outputting second feedback concurrently with the first feedback, the second feedback indicating keystroke input according to the second context.

45. The method of claim 37, further comprising:

accepting a backspace keystroke;

deleting a keystroke from the keystroke sequence;

repeating the steps of determining whether the keystroke sequence produces a valid result in a first context, and, responsive to the key-stroke sequence producing a valid result in the first context, outputting first feedback, the first feedback indicating keystroke input according to the first context; and

repeating the steps of responsive to the keystroke sequence not producing a valid result in the first context, determining whether the keystroke sequence produces a valid result in a second context, and, responsive to the keystroke sequence producing a valid result in the second context, outputting second feedback concurrently with the first feedback, the second feedback indicating keystroke input according to the second context.

46. The method of claim 37, wherein the first context comprises accepting input for a direct entry operation.

47. The method of claim 46, wherein the direct entry operation comprises a telephone number direct entry operation.

48. The method of claim 46, wherein determining whether the keystroke sequence produces a valid result in the first context comprises determining whether all of the accepted keystrokes have a numeric value.

49. The method of claim 37, wherein the first context comprises accepting input for a directory filtering operation, and the second context comprises accepting input for a direct entry operation.

50. The method of claim 37, wherein accepting a keystroke sequence comprises accepting a keystroke sequence entered via a QWERTY keyboard having a plurality of keys, wherein a subset of the keys have secondary numeric values.

51. The method of claim 50, wherein the subset of the keys having secondary numeric values are arranged according to a numeric keypad layout.

52. A system for concurrently accepting parameters in at least two contexts, the system comprising:

a character input device comprising a plurality of character input device elements, each character input device element having a first value, and at least a subset of the character input device elements having a second value;

28

a buffer, coupled to the character input device, for storing a keystroke sequence entered on the character input device, the keystroke sequence comprising at least one keystroke;

a string handler, coupled to the buffer, for determining whether the keystroke sequence produces a valid result in a first context and for determining whether all of the keystrokes are valid in a second context;

an output device, coupled to the string handler, for: responsive to the keystroke sequence producing a valid result in the first context, outputting first feedback, the first feedback indicating keystroke input according to the first context; and

responsive to the keystroke sequence not producing a valid result in the first context and producing a valid result in the second context, outputting second feedback, the second feedback indicating keystroke input according to the second context; and

a processor, coupled to the string handler, for: responsive to the keystroke sequence producing a valid result in the first context, performing a first action corresponding to the first context, using the first value for each keystroke; and

responsive to the keystroke sequence not producing a valid result in the first context and producing a valid result in the second context, performing a second action corresponding to the second context, using the second value for each keystroke.

53. The system of claim 52, wherein the processor comprises:

a directory lookup engine and a dialer, and wherein the first action comprises retrieving a telephone number from a directory record identified by the first value for each keystroke and

dialing the retrieved telephone number.

54. The system of claim 52, wherein the processor comprises

a dialer, coupled to the string handler, and wherein the second action comprises dialing a telephone number specified by the second value for each keystroke.

55. The system of claim 52, wherein:

the output device comprises a display screen;

the character input device comprises a keyboard; and

each character input device element comprises a key.

56. The system of claim 52, further comprising:

a second output device, coupled to the string handler, for, responsive to the keystroke sequence not producing a valid result in the first context and not producing a valid result in the second context, outputting an invalidity indicator.

57. The system of claim 56, wherein the second output device comprises at least one selected from:

an auditory output device; and

a visual output device.

58. The system of claim 52, wherein, responsive to the keystroke sequence not producing a valid result in the first context and not producing a valid result in the second context, the output device outputs an invalidity indicator.

59. The system of claim 52, wherein the first context comprises accepting input for an iterative directory filtering operation on a plurality of directory records.

60. The system of claim 59, further comprising:

a directory filter, coupled to the string handler, for, responsive to the keystroke sequence producing a valid result in the first context, performing the directory filtering operation using the first value for each of the stored keystrokes.



61. The system of claim 52, wherein at least one of the contexts comprises accepting input for a direct entry operation.

62. The system of claim 61, wherein the first context comprises accepting input for a direct entry operation.

63. The system of claim 62, wherein the direct entry operation comprises a telephone number direct entry operation.

64. The system of claim 52, wherein the first context comprises accepting input for a directory filtering operation, and the second context comprises accepting input for a direct entry operation.

65. The system of claim 52, wherein:

each first value comprises one selected from the group consisting of a letter and a punctuation symbol; and each second value comprises a number.

66. The system of claim 52, wherein:

each first value comprises one selected from the group consisting of a letter and a punctuation symbol; and each second value comprises one selected from the group consisting of a number and a punctuation symbol.

67. The system of claim 52, wherein:

responsive to at least one of the keystrokes not being valid in one of the contexts, the string handler determines that the other context is intended.

68. The system of claim 52, wherein the character input device comprises a QWERTY keyboard having a plurality of keys, wherein a subset of the keys have secondary numeric values.

69. The system of claim 68, wherein the subset of the keys having secondary numeric values are arranged according to a numeric keypad layout.

70. A system for concurrently accepting parameters in at least two contexts, the system comprising:

a character input device comprising a plurality of character input devices, each character input device having a first value, and at least a subset of the character input devices having a second value;

a buffer, coupled to the character input device, for storing a keystroke sequence entered on the character input device, the keystroke sequence comprising at least one keystroke;

a string handler, coupled to the buffer, for determining whether the keystroke sequence produces a valid result in a first context and for determining whether all of the keystrokes are valid in a second context;

an output device, coupled to the string handler, for:

responsive to the keystroke sequence producing a valid result in the first context, outputting first feedback, the first feedback indicating keystroke input according to the first context; and

responsive to the keystroke sequence producing a valid result in the second context and not producing a valid result in the first context, outputting second feedback, the second feedback indicating keystroke input according to the second context;

responsive to the keystroke sequence producing a valid result in both the first and second contexts, outputting first and second feedback concurrently, the first feedback indicating keystroke input according to the first context and the second feedback indicating keystroke input according to the second context;

wherein, responsive to the keystroke sequence producing a valid result in the first context, the system performs a first action corresponding to the first context, using the first value for each keystroke; and

wherein, responsive to the keystroke sequence producing a valid result in the second context, the system performs a second action corresponding to the second context, using the second value for each keystroke; and

wherein, responsive to the keystroke sequence producing a valid result in both the first and second contexts, the system performs a first action corresponding to the first context, using the first value for each keystroke, and a second action corresponding to the second context, using the second value for each keystroke.

71. The system of claim 70, wherein:

the output device comprises a display screen;

the character input device comprises a keyboard; and

each character input device element comprises a key.

72. The system of claim 71, wherein the display screen outputs the first visual feedback at a first location and outputs the second visual feedback at a second location.

73. The system of claim 70, wherein the first context comprises accepting input for an iterative directory filtering operation on a plurality of directory records.

74. The system of claim 70, wherein at least one of the contexts comprises accepting input for a direct entry operation.

75. The system of claim 74, wherein the first context comprises accepting input for a direct entry operation.

76. The system of claim 75, wherein the direct entry operation comprises a telephone number direct entry operation.

77. The system of claim 70, wherein the first context comprises accepting input for a directory filtering operation, and the second context comprises accepting input for a direct entry operation.

78. The system of claim 70, wherein the character input device comprises a QWERTY keyboard having a plurality of keys, wherein a subset of the keys have secondary numeric values.

79. The system of claim 78, wherein the subset of the keys having secondary numeric values are arranged according to a numeric keypad layout.

80. A computer program product comprising a computer-usable medium having computer-readable code embodied therein for concurrently accepting parameters in at least two contexts, the computer program product comprising:

computer-readable program code configured to cause a computer to accept a keystroke sequence comprising at least one keystroke, each keystroke having a first value, and at least one keystroke having a second value;

computer-readable program code configured to cause a computer to determine whether the keystroke sequence produces a valid result in a first context;

computer-readable program code configured to cause a computer to, responsive to the keystroke sequence producing a valid result in the first context:

output first feedback, the first feedback indicating keystroke input according to the first context; and perform a first action corresponding to the first context, using the first value for each keystroke;

computer-readable program code configured to cause a computer to, responsive to the keystroke sequence not producing a valid result in the first context:

determine whether the keystroke sequence produces a valid result in a second context; and

responsive to the keystroke sequence producing a valid result in the second context:

output second feedback, the second feedback indicating keystroke input according to the second context; and

perform a second action corresponding to the second context, using the second value for each keystroke.

**81.** The computer program product of claim **80**, wherein the first context comprises accepting input for an iterative directory filtering operation on a plurality of directory records.

**82.** The computer program product of claim **81**, wherein:  
the computer-readable program code configured to cause  
a computer to perform a first action corresponding to  
the first context comprises computer-readable program  
code configured to cause a computer to perform the  
directory filtering operation using the first value for  
each of the accepted keystrokes.

**83.** The computer program product of claim **80**, wherein at least one of the contexts comprises accepting input for a direct entry operation.

**84.** The computer program product of claim **83**, wherein the first context comprises accepting input for a telephone number direct entry operation.

**85.** The computer program product of claim **80**, wherein the computer-readable program code configured to cause a computer to determine whether the keystroke sequence produces a valid result in a first context comprises computer-readable program code configured to cause a computer to determine whether all of the accepted keystrokes have a numeric value.

**86.** The computer program product of claim **80**, wherein the first context comprises accepting input for a directory filtering operation, and the second context comprises accepting input for a direct entry operation.

**87.** The computer program product of claim **80**, further comprising:

computer-readable program code configured to cause a computer to, responsive to at least one of the accepted keystrokes not being valid in one of the contexts, determine that the other context is intended.

**88.** The computer program product of claim **80**, further comprising:

computer-readable program code configured to cause a computer to, responsive to the keystroke sequence not producing a valid result in one of the contexts, perform an action using the keystroke sequence according to the other context.

**89.** The computer program product of claim **80**, wherein the computer-readable program code configured to cause a computer to accept a keystroke sequence comprises computer-readable program code configured to cause a computer to accept a keystroke sequence from a QWERTY keyboard having a plurality of keys, wherein a subset of the keys have secondary numeric values.

**90.** The computer program product of claim **89**, wherein the subset of the keys having secondary numeric values are arranged according to a numeric keypad layout.

**91.** The computer program product of claim **80**, wherein the computer-readable program code configured to cause a computer to accept a character sequence comprises computer-readable program code configured to cause a computer to accept a character sequence from a QWERTY keyboard having a plurality of keys, wherein a subset of the keys have secondary numeric values.

**92.** The computer program product of claim **91**, wherein the subset of the keys having secondary numeric values are arranged according to a numeric keypad layout.

**93.** A computer program product comprising a computer-usable medium having computer-readable code embodied therein for concurrently accepting parameters in at least two contexts, the computer program product comprising:

computer-readable program code configured to cause a computer to accept a keystroke sequence comprising at least one keystroke, each keystroke having a first value, and at least one keystroke having a second value;

computer-readable program code configured to cause a computer to determine whether the keystroke sequence produces a valid result in a first context;

computer-readable program code configured to cause a computer to, responsive to the keystroke sequence producing a valid result in the first context, output first feedback, the first feedback indicating keystroke input according to the first context, and to perform a first action corresponding to the first context, using the first value for each keystroke;

computer-readable program code configured to cause a computer to, responsive to the keystroke sequence not producing a valid result in the first context:

determine whether the keystroke sequence produces a valid result in a second context; and

responsive to the keystroke sequence producing a valid result in the second context, output second feedback, the second feedback indicating keystroke input according to the second context, and to perform a second action corresponding to the second context, using the second value for each keystroke.

**94.** The computer program product of claim **93**, wherein: the computer-readable program code configured to cause a computer to output the first visual feedback comprises computer-readable program code configured to cause a computer to output the first feedback at a first location on a display screen; and

the computer-readable program code configured to cause a computer to output the second visual feedback comprises computer-readable program code configured to cause a computer to output the second feedback at a second location on a display screen.

**95.** The computer program product of claim **93**, wherein the first context comprises accepting input for an iterative directory filtering operation on a plurality of directory records.

**96.** The computer program product of claim **93**, wherein the first context comprises accepting input for a telephone number direct entry operation.

**97.** The computer program product of claim **93**, wherein the computer-readable program code configured to cause a computer to accept a keystroke sequence comprises computer-readable program code configured to cause a computer to accept a keystroke sequence from a QWERTY keyboard having a plurality of keys, wherein a subset of the keys have secondary numeric values.

**98.** The computer program product of claim **97**, wherein the subset of the keys having secondary numeric values are arranged according to a numeric keypad layout.

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 6,950,988 B1  
APPLICATION NO. : 09/976477  
DATED : September 27, 2005  
INVENTOR(S) : Jeffrey C. Hawkins et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 23,


Line 1, replace "fist" with -- first --.

Column 29,

Line 55, replace "-first" with -- first --.

Signed and Sealed this

Twenty-seventh Day of June, 2006

A handwritten signature in black ink on a light gray dotted background. The signature is written in a cursive style and reads "Jon W. Dudas".

JON W. DUDAS

*Director of the United States Patent and Trademark Office*